

## Specifications



The DocuPrint 2000 Series EPS will help you to consistently meet mission-critical deadlines while maintaining a cost-efficient production environment. Achieving true efficiency requires value-added solutions that combine fast, reliable printers with the right software and finishing equipment to match your overall business goals.

The DocuPrint 2000 Series EPS allows you to streamline production processes, shorten turnaround times, and lower operating costs for the entire production process.

Impressive speeds—up to 96, 115, or 135 ppm—unparalleled reliability and quality, and all of the experience from the company that invented transactional variable data printing make DocuPrint 100/100MX, 115/115MX and 135/135MX EPS the best choice to put your document production on the fast track.

# Xerox DocuPrint

100/100MX • 115/115MX • 135/135MX

## Enterprise Printing Systems





For more information on the Xerox DocuPrint® 100/115/135 Enterprise Printing Systems, call **1-800 ASK XEROX** or visit us on the Web at: [www.xerox.com](http://www.xerox.com)

## Xerox DocuPrint 100/100MX • 115/115MX • 135/135MX Enterprise Printing Systems Specifications

### System Control Module

- Sun Blade 1000
- Dual 750 MHz UltraSparc III processors
- 36 GB system disk
- 2 GB memory
- DVD-ROM Drive, QIC tape
- 17.4 inch color flat panel display
- Keyboard and mouse
- Ethernet interface (10/100BaseT)
- Two image processing printer interface cards
- Controller stand (optional)
- 18/36-track tape drive (optional)

### Printer Module

- Xerographic engine with laser raster imaging system
- Prints simplex or duplex
- Monthly duty cycle: up to 3 million (DP 100), 3.5 million (DP 115), or 4 million (DP 135) impressions
- Printer control console shows current printer status
- Operator attention light

### MICR (Magnetic Ink Character Recognition)

- Check performance guarantee
- Consistently exceeds 99.5% read rate
- Uniformity—maintain a signal strength across all characters
- Consistency—maintain uniformity from check to check and under a range of environmental conditions
- Durability—maintain image permanence in high-speed readers/sorters

### Datastream Support

#### DocuSP® Common Controller:

- Adobe PostScript® level 3, PDF, HP PCL5e, TIFF, ASCII, VIPP® Software
- LCDS/Metacode (option)
- NPS Extension (option):
  - PostScript level 2, HP PCL5e, ASCII, VIPP
- IPDS Printing (option):
  - Emulates an IBM Printing Systems AFP Group 3 page printer with the AFIG (Advanced Function Image and Graphics) option

### Speed

- Print speeds:
  - DocuPrint 100: Up to 96 ppm. (8.5 by 11 in./A4)
  - DocuPrint 115: Up to 115 ppm. (8.5 by 11 in./A4)
  - DocuPrint 135: Up to 135 ppm. (8.5 by 11 in./A4)

### Paper Handling

- 16 to 110 lb. (60 to 200 gsm) cut-sheet paper weights
- 7 by 10 in. (optional) to 14 by 17 in. (178 by 254 mm to 356 by 432 mm including A4, A3, B4) paper sizes
- Transparencies, label stock, tab stock, carbonless paper, pre-perforated stock, safety stock, and other specialized application materials

#### Input:

- Main tray (tray 1): 1,100-sheet capacity of 20 lb. (80 gsm) stock
- Auxiliary tray (tray 2): 600-sheet capacity of 20 lb. (80 gsm) stock
- Two high-capacity feeders (trays 3 and 4): 2,600 sheets each of 20 lb. (80 gsm) stock (standard)
- Up to two additional high-capacity feeders (optional): 2,600 sheets each of 20 lb. (80 gsm) stock input trays
- 7 by 10 in. (178 by 254 mm) enablement kit: enables feeding of paper as small as 7 by 10 in. (optional)

#### Output:

- Two high-capacity stackers (standard); up to two additional high-capacity stackers (optional). Each 2,500-sheet capacity of 20 lb. (80 gsm) stock
- Sample tray: 100 sheets of 20 lb. (80 gsm) stock
- Purge tray: 100 sheets of 20 lb. (80 gsm) stock
- Bypass transport: enables connection to any DFA-compliant, third-party inline finishing device (optional)\*

### Modular Trade In (MTI)

- On-site upgrades without hardware changes to the printer module
- Move from one configuration to another with MTI
  - 100 to 115 configuration
  - 100 to 135 configuration
  - 115 to 135 configuration

### Connectivity

#### DocuSP Common Controller:

##### LCDS:

- IBM Channel, Ethernet TCP/IP (LRS VPS and XPAF only), off-line tape\*

##### Network:

- Ethernet: TCP/IP, Netware, AppleTalk
- Token Ring: TCP/IP, Netware, AppleTalk

##### NPS Extension (option):

- Ethernet: TCP/IP, Netware, AppleTalk
- Token Ring: TCP/IP, Netware AppleTalk

##### IPS Extension (option):

- Ethernet TCP/IP, Token Ring TCP/IP
- S/370 or S/390 bus and tag

### Resolution

- 600-dpi input imaged at 600 x 2400 dpi
- 300-dpi input converted to produce 600 x 2400-dpi imaging

### Environmental Requirements

- Recommended operating temperature: 72° ±4°F (22° ±2°C)
- Minimum/maximum operating temperature: 50° to 85°F (10° to 29°C)
- Minimum/maximum relative humidity: 45% ± 10% (no condensation)
- Maximum normal altitude: up to 6,000 ft./1830 m above sea level
- Audible noise level: meets 82dB noise exposure limit
- Heat dissipation, in Btu per hour
  - System control module: 3,074 Btu
  - Printer module: 4,454 standby; 28,140 operating

### Electrical Requirements

- System control module: 100-240 VAC, 50-60 Hz, 12 amp
- Printer module: (one of possible configurations listed below)
  - Cord System: 120/208 VAC (2 Phase), 60 Hz, 50 amp dedicated service
  - Star: 220/380 VAC or 230/400 VAC or 240/415 VAC (3 Phase), 50 Hz, 30 amp dedicated service
  - Delta: 220 VAC or 230 VAC or 240 VAC (3 Phase), 50 Hz, 30 amp dedicated service
- Agency certification: UL, CSA, CE Mark

### Physical Characteristics

Width in. (mm)	Depth in. (mm)	Height in. (mm)	Weight lbs. (kg)
<b>System Control Module</b>			
10.0 (254)	24.0 (610)	17.9 (455)	70 (32)
<b>Printer Module, including Printer Control Console</b>			
77.3 (1,963)	35.9 (911)	55.0 (1,397)	1,434 (651)
<b>High-Capacity Inverter Feeder/Stacker</b>			
41.7 (1,060)	28.3 (719)	57.7 (1,466)	663 (301)
<b>High-Capacity Feeder/Stacker Middle Module (optional)</b>			
32.4 (822)	28.3 (719)	57.7 (1,466)	521 (237)
<b>High-Capacity Feeder/Stacker</b>			
32.4 (822)	28.3 (719)	59.6 (1,513)	521 (237)
<b>Bypass Transport (optional)</b>			
20.4 (518)	28.3 (719)	56.1 (1,425)	176 (80)

\*Please check with your Xerox representative for availability.



©2002 XEROX Corporation. All rights reserved. XEROX®, The Document Company®, X® (stylized), DocuPrint®, DocuSP®, and VIPP® are trademarks of or licensed to Xerox Corporation. The Xerox Total Satisfaction Guarantee applies to equipment under a Xerox warranty or a Full Service Maintenance Agreement and is subject to certain conditions. Product appearance, build status and/or specifications are subject to change without notice. 10/02. 610P713990